

THE MODIFICATION OF SOIL STRUCTURE OVER DIFFERENT TECHNOLOGICAL VARIANTS, IN BEAN CROPS FROM THE MOLDAVIAN PLAIN

L. RĂUS

University of Agricultural Sciences
and Veterinary Medicine
“Ion Ionescu de la Brad” Iassy
e-mail: rauslucian@univagro-iasi.ro

Optimal crop rooting soil physical conditions are a result of complex interactions between soil strength and oxygen and water supply to plant roots. Spatial/temporal variability in soil properties can be critical in the evaluation of the effects of tillage management practice on soil and crop parameters. In this paper tillage were evaluated for theirs effects on soil structure. Tillage treatments were plough to 20 cm, plough to 30 cm, chisel and disc harrow applied to wheat in to been/ wheat/ maize rotation. The experiments have been conducted in the Didactic Station of the University of Agricultural Sciences and Veterinary Medicine – Iasi, Ezăreni Farm, during the period between 2002-2005, on a cambic chernozem with 3,4 % humus and pH 7. Tillage system modify, at least temporarily, some of the structure properties of soil, such structural stability, distribution of aggregates, qualitative indices and mean diameter. All the tillage operation was significantly different in their effects on soil properties.

Keywords: soil tillage, soil structure, structural stability, qualitative indices of structure.

In modern conceptions, soil structure is one of the essential characteristics with direct influences on all physical, mechanical and biological processes, which take place in soil (Arshad M. & al. 1997, Brown D. & al., 1996, Drescher J. & al., 1988, Horn R. & al., 1994, 2005, Dexter A., 1988). Vast investigations, carried out by many authors, have reflected the multiple relations between soil structural characteristics and plant growth (Barbora Badalikova and Hurby J., 2006, Beare M. & al., 1997). According to size, form and forming mode, the aggregates may have more or less characteristics favorable to the circulation of water and air, and root penetration (Iris Vogeler & al., 2006).

MATERIAL AND METHOD

The experiments have been conducted in the Experimental Farm of Agricultural University Iasi between 2002-2005, on a cambic chernozem with 3,4 % humus and 7,0 pH value. The treatments were arranged in a split-plot design and replicated three times. Tillage treatments were plough to 20 cm, plough to 30 cm, working with chisel

and with disc harrow and two different fertilizations levels applied to three crops species (been/ wheat/ maize rotation).

This paper presents the results on the influence of tillage method on the indicators of soil structure characterization. The analysis of distribution and structure hydrostability of structural macroaggregates was carried out according to Tiulin-Ericson method, and certain indicators as mean weighed diameter, quality indices of structure and aggregation index, were determined by calculation (Canarache A., 1990).

RESULTS AND DISCUSSION

At sowing, the aggregates with higher than 5 and 10 mm diameter were prevalent in variants tilled without furrow inverting. In Chisel-tilled variant, the aggregate categories with \varnothing between 1 and 5 mm were prevalent, and aggregates with $\varnothing < 1$ mm were found at the highest rate. In the layer of 0-10 cm, after conservation works, the ratio between different aggregate categories from the present situation at sowing was changed, the weight of aggregates with $\varnothing = 1$ mm being increased. On the last stage of studied depth, where the influence of equipments used for conservation works was not signaled, the aggregates > 5 mm were prevalent in all variants.

Until harvesting, a slight increase in the proportion of structural elements with 3, 5 and 10 mm diameter was found and simultaneously, a diminution in the proportion of small size diameter aggregates, especially in the surface layer.

At the last studied depth, there were no great differences compared to previous period, a slight increase in aggregate proportion with higher diameter being noticed.

Table 1

„Mean weighed diameter” to bean crop – mean values on variant, depth and stages of growing, 2002-2005

Tillage systems	Mean weighed diameter		Difference (mm)	Significance
	\varnothing aggregates (mm)	% /C.V.		
Chisel	6.35	114.2	0.8	xx
Plough to 20 cm	5.93	106.7	0.4	
Plough to 30 cm	5.69	102.3	0.1	
Disk harrow	4.27	76.8	-1.3	ooo

Control variant (C.V.) – mean value for all variants

LSD _{5%} = 0.4 (% v/v)

LSD _{1%} = 0.5 (% v/v)

LSD _{0,1%} = 0.9 (% v/v)

The mean weighed diameter (MWD) was better emphasized (*tab. 1*). At sowing, the structural elements of great size were prevalent, excepting the disk harrow-tilled variant. The Chisel- tilled variant favored the formation of great diameter structural elements, especially at depths below 10 cm, where there was less influence of equipments used for seedbed preparation. The conservation works have determined the destruction of great size aggregates. In this period, the aggregates lower than 3 mm diameter were prevalent. This phenomenon was felt until the depth of 15-20 cm, but below this depth, the mean diameter of structural

elements continued to have great values. Until harvesting, the stress caused by conservation equipments lacking, the aggregation degree was improved, the mean weighed diameter increasing in depth at all the variants.

The statistical analysis of mean values has shown that the Chisel tillage has favored the most the aggregation of soil particles with optimum size and adequate proportion. The *mean weighed diameter* of structural elements had a distinctively significant difference to the average value (control).

Disk harrow tillage, combined with conservation works, resulted in mechanical destruction of aggregates, this assessment being supported by statistically insured differences (*tab. 1*).

The *structure hydrostability* increased once with the depth in all the variants of soil tillage, indifferently of vegetation stage. At sowing, in layer 0-10 cm, the values of the index were the highest for the entire vegetation period.

The highest values were found in ploughed variants, due to structure hydrostability of soil, which was brought from depth. At depth of 10-20 cm, the structure hydrostability had close values, except the case of the disk harrow-tilled variant, where the values were lower than in the other variants. At depth of 20-30 cm, the structure hydrostability was balanced, having close values for all variants.

After carrying out conservation works, minimum values were registered in layers 0-10 and 10-20 cm, and until harvesting, the structure hydrostability has increased, indifferently of tillage system, at all depths, reaching maximum values in layer 20-30 cm, at ploughed variants.

The tilled variants without furrow inverting have determined the highest values of structure hydrostability in upper layers 0-10 and 10-20 cm, and the chisel-tilled variant had, on the average, the best structure hydrostability at depths of 20-30 cm. The disk harrow-tilled variant was separated, in negative sense, from the other variants (*tab. 2*).

Table 2

Structure hydrostability in bean crop – mean values/ variant, depth and vegetation stage, 2002-2005

Tillage systems	Structure hydrostability		Difference (mm)	Significance
	Ø aggregates (mm)	% / C.V.		
Plough to 20 cm	57.8	104.1	2.3	xxx
Plough to 30 cm	57.7	103.9	2.2	xx
Chisel	56.7	102.2	1.2	xx
Disk harrow	49.8	89.7	-5.7	ooo

Control variant (C.V.) – mean value for all variants

LSD _{5%} = 0.7 (% v/v)

LSD _{1%} = 1.1 (% v/v)

LSD _{0,1%} = 1.8 (% v/v)

The analysis of mean values on profile and for the entire vegetation period has classified the variants according to data presented in table 4, the differences between variants being greater, and the differences compared to the control, statistically insured. The best structure hydrostability on analyzed profile was determined at the 20 cm ploughed variant, due to higher values of the indicator at

depths of 20-30 cm, in comparison with the same depth for the 30 cm ploughed variant. In comparison with the control, the statistically insured negative differences were found only at the disk harrow-tilled variant.

Qualitative indices. These indicators of the structure quality have shown that it varied in vegetation according to soil mobilization degree. We pointed out that in surface layer the structure was damaged during the conservation works (*tab. 3*). Its quality could be considered as bad, because of the high weight of aggregates from categories IV, V and VI, to the disadvantage of those from categories I, II and III. In Chisel-tilled variant the organic matter which remained at soil surface, protected the aggregates from groups I, II and III; this was shown by greater values of I_1 indicator (0.4 compared to 0.2 at all the other variants), indicating a greater participation of >3 mm aggregates and a reduced participation of I_2 indicator (0.3 compared to 0.4 or 0.5). It showed a reduced participation of 2 mm aggregates compared to the ones with lower diameter. Until harvesting, the structure quality was improved at all variants, being better on profile, in case of ploughed variants.

Table 3

Structure quality indices to bean crop – mean values, 2002-2005

Tillage systems	Depth (cm)	Structure quality indices						The aggregation indices		
		I ₁			I ₂					
		Sem.	Veg.	Rec.	Sem.	Veg.	Rec.	Sem.	Veg.	Rec.
Plough to 30 cm	0-10	0.8	0.2	0.5	0.9	0.5	0.5	40.4	42.6	46.2
	10-20	1.2	1.0	0.8	0.6	0.6	0.8	41.0	46.3	45.8
	20-30	1.0	0.9	1.3	0.9	1.2	1.8	43.1	42.6	43.2
	Mean	1.0	0.7	0.9	0.8	0.7	1.0	41.5	43.8	45.1
Plough to 30 cm	0-10	0.8	0.2	0.7	0.9	0.4	0.5	40.2	44.7	45.1
	10-20	1.1	0.8	0.8	0.6	0.6	0.6	40.3	43.6	45.5
	20-30	0.8	0.9	1.2	0.8	0.7	0.9	45.6	43.4	46.1
	Mean	0.9	0.6	0.9	0.8	0.6	0.7	42.0	43.9	45.6
Chisel	0-10	0.6	0.4	0.5	0.6	0.3	0.4	42.2	41.9	43.0
	10-20	1.1	1.0	1.1	0.8	0.8	1.0	38.7	42.9	43.9
	20-30	1.2	0.6	0.8	1.2	1.3	2.1	41.1	41.6	42.9
	Mean	1.0	0.7	0.8	0.9	0.8	1.2	40.7	42.1	43.3
Disk harrow	0-10	0.2	0.2	0.2	0.5	0.3	0.4	40.6	36.9	38.2
	10-20	0.3	0.4	0.4	0.5	0.7	0.7	38.5	41.0	39.4
	20-30	1.4	1.6	1.7	1.4	2.3	3.1	44.6	44.3	44.2
	Mean	0.6	0.7	0.8	0.8	1.1	1.4	41.2	40.7	40.6

The analysis of hydrostable aggregates to total percentage has shown that on studied profile, the structural elements from ploughed variants were more stable at spreading action of water. The values of aggregation index have increased at depth and during vegetation period at all the variants, excepting the disk harrow-tilled variant (below the depth of 10 cm), because of the stress caused by soil continuous settling at this variant, which deteriorate the structure quality with time.

CONCLUSIONS

1. The mean weighed diameter has registered a diminution in vegetation period on layers 0-10 and 10-20 cm, and a slight increase until harvesting. At the depth of 20-30 cm, where the effect of conservation works was not felt, the diameter of aggregates has increased constantly until harvesting.

2. Unlike the other variants, aggregates with great diameter were prevalent in the Chisel-tilled variant, because of accumulation and decay of organic matter at soil surface; this favored the intensification of structure formation. This was found, too, at the depth at which soil was not mobilized through base tillage (20-30 cm), especially in Chisel-tilled and 20 cm ploughed variants.

3. The structure hydrostability, indifferently of the vegetation stage or tillage variant, has increased once with depth, reaching maximum values in the layer 20-30 cm, at ploughed variants. The tilled variants without furrow inverting had high values of structure hydrostability in upper layers (0-10 and 10-20 cm). The Chisel-tilled variant had, on the average, the best structure hydrostability, at depth of 20-30 cm.

4. The qualitative indices of soil structure had a high value during vegetation period until harvesting, indifferently of tillage system. This has shown that during vegetation, a modification of hydrostable aggregate participation and creation of a more favourable ratio between them resulted in increasing structure quality. The analysis of mean values at depth of 0-30 cm in qualitative indices of soil structure has shown that, although structure hydrostability and aggregation index had higher values in ploughed variants (especially at 30 cm ploughing), the structure quality and ratio between structure hydrostability were higher in Chisel-tilled variant, compared to the other variants.

5. The analysis of the percentage of hydrostable aggregates, compared to the total percentage of aggregates, has shown that on studied profile, the structural aggregates formed in ploughed variants with furrow inverting were more stable to the spreading action of water than in the other variants.

6. In case of 20 cm ploughed and below 20 cm disk harrow-tilled variants, where the effect of soil mobilization is no longer felt, the structure quality (according to I1 și I2) was better than in the case of every year soil mobilization.

BIBLIOGRAPHY

1. Barbora Badalikova, Hurby J., 2006 - *Influence of minimum soil tillage on development of soil structure*. International Soil Tillage Research Organisation 17 th Triennial Conference, Kiel, Germany.
2. Beare M. H., Hu S., Coleman D.C., Hendrix P.F., 1997 - *Influences of mycelial fungi on soil aggregation and organic matter storage in conventional and no-tillage soils*. Applied Soil Ecology, 5 (3), 211-219.
3. Brown D., Dexter A.R., Chamen W.C.T., Spoor G., 1996 - *Effect of soil macroporosity and aggregate size on seed-soil contact*. Soil and Tillage Research, 38, 203-216.
4. Canarache Andrei, 1990 - *Fizica solurilor agricole*. Editura Ceres, București.

5. Dexter A.R., 1988 - *Advances in characterization of soil structure*. Soil and Tillage Research, 11, 199-238.
6. Iris Vogeler, Rainer Horn, Holger Wetzel, Julia Krummelbein, 2006 - *Tillage effects on soil strength and solute transport* - Soil & Tillage Research 88, 193–204.
7. Drescher J., Horn R., M. de Boodt, 1988 - *Impact of water and external forces on soil structure*. Catena supplement 11. GeoScience Publisher, Germany.
8. Horn R., Taubner H., Wuttke M., Baumgart, Th., 1994 - *Soil physical properties related to soil structure*. Soil and Tillage Research, 30, 187-216.
9. Horn R., H. Fleige a, F.-H. Richter a, E.A. Czyz c, A. Dexter, E. Diaz-Pereira, E. Dumitru , R. Enarche, F. Mayol, K. Rajkai, D. de la Rosa, C. Simota, 2005 - *SIDASS project Part 5: Prediction of mechanical strength of arable soils and its effects on physical properties at various map scales*. Soil & Tillage Research 82, 47–56.
10. Jităreanu G., L. Răus, D Topa, 2006 - *Dinamica elementelor nutritive în diferite variante tehnologice de lucrare a solului*. Lucrari stiintifice, seria Agronomie, Iasi, 49.